

MT221DN / MT224DN

Color Dome Camera



MT 221 / 224 DN

Features:

- MT221DN, MT224 DN 1/3" Sony Super HAD CCD
- 3.6mm wide lens
- Dome can be easily removed from mounting base without dismounting the mounting base from the ceiling, for maintenance purpose
- Dome can be rotate in horizontal axis to obtain best view angle without the hassle of removing the cover
- Auto changeover Day and Night Function
- Small and compact design. No bulky camera tangling on the ceiling

Specification:

Model		MT221DN	MT224DN
Image sensor		1/3" SONY SUPER HAD CCD	
Resolution		420 TVL	520 TVL
Total Pixels (HxV)	PAL	500(H) x 582(V)	752(H) x 582(V)
Scanning Frequency		PAL: 15.625 KHz(H), 50Hz(V)	
Scanning System		2:1 Interlace	
S/N Ratio		More than 52dB (AGC Off)	
Min. Illumination		0.8 LUX	0.5 LUX
Sync. System		Synchronization	
Electronic Shutter		PAL: 1/50 sec	
Gamma		Y = 0.45	
Video Output		1.0 Vp-p Composite (75Ω)	
AGC		Auto	
Power Requirement		DC12V (±10%)	
Power Consumption		100mA	
Cable		BNC/DC JACK	
Operation Temp		-10°C ~ +50°C RH95% MAX	
Storage Temp		-20°C ~ +60°C RH95% MAX	
Lens		3.6mm Fix board lens	

© COPYRIGHT Oct 2007. This documentation served as a reference only. It is subject to change without further notice. All the diagrams and information in this documentation may not be duplicated or modified in any form without the written approval from the management.