



**CPT-868
CONTROL UNIT**



**CPT-870
Remote Control**



**CPT-864
Passive
Motion Detector**



**CPT-872
Wireless Gas Detector**



**CPT-871
Wireless
Smoke Detector**



**CPT-873
Magnetic
Transmitter**

**CPT-873
Vibration Detector**

Authorised Dealer

MODEL NO.	CPT-868	CPT-864	CPT-870	CPT-871	CPT-872	CPT-873
VOLTAGE	DC 12V Adaptor	9V Alkaline Battery	12V Alkaline Battery	9V Alkaline Battery	230AC	12V Alkaline Battery
STANBY CURRENT	100mA	< 2.5mA	0µA	Under 2.5µA	1W	0µA
FREQUENCY	Oscillated by SAW Resonator 320	Oscillated by SAW Resonator 320	Oscillated by SAW Resonator 320	Oscillated by SAW Resonator 320	Oscillated by SAW Resonator 320	Oscillated by SAW Resonator 320
TEMPERATURE	-	0°C - 40°C	-	0°C - 50°C	-10°C to 50°C	-
BROADCAST RANGE	No Obstruction 100 Feet	No Obstruction 30 Feet	No Obstruction 100 Feet	-	-	No Obstruction 100 Feet
DIMENSION (MM)	230 x 175 x 60	91 x 63 x 45	65 x 40 x 11	∅ 84 x 77 x 93 x 66 x 24	140 x 85 x 40 +93 x 66 x 240	62 x 38 x 16
WEIGHT (GM)	1150gm	100gm	40gm	280gm	500gm	40gm

* Specification are Subject to Change without Prior Notice